



Technical Data Sheet

Solder Spheres — Sn10Pb90 | Rev. 8 — July 2026

Product Overview

EasySpheres Sn10Pb90 solder spheres are manufactured and designed to support optimized ball-attach applications for ball grid array (BGA) and chip scale package (CSP) components, as well as BGA rework and rebonding. Spheres are packaged to resist the surface darkening induced by transit tumbling, reducing machine-vision faults in automated ball placement systems. Product ships in medical-grade, ESD-safe containers, conforms to IPC J-STD-006, and is QR-coded for lot conformance traceability and shipping accuracy.

Alloy Composition Analysis (Wt%) — per IPC J-STD-006C

Item per J-STD-006	Physical Property			Main Component		Impurities (max)								
	Solidus °C	Liquidus °C	Spec. Wt.	Sn	Pb	Sb	Cu	Bi	Zn	Fe	Al	As	Cd	Other
Standard Limits	268	302	10.70	10 ±0.5	90 ±0.5	0.20	0.0800	0.1000	0.0030	0.0200	0.0050	0.0300	0.0020	0.0000

Typical Alloy Properties — Sn10Pb90

Density	10.75 g/cm ³	Electrical Resistivity	≈ 19.4 μΩ·cm
CTE (25°C)	≈ 28 ppm/°C	Tensile Strength	≈ 30 MPa (4,400 psi)
Thermal Conductivity	≈ 25 W/m·K	Elongation	≈ 30%

Typical published values for the alloy, provided for engineering reference; not a lot-specific certification. Lot-specific composition is certified on the Certificate of Conformance accompanying each shipment.

Dimensional Tolerances

Size Range (mm)	Max Dimensional Tolerance	Typical / Actual Measured Tolerance	Sphericity Deviation	Inspection Illuminance
0.050 – 0.450	±4%	±0.50%	< 1.5%	> 270 lux
0.500 – 0.550	±4%	±1%	< 1.5%	> 270 lux
0.600 – 0.889	±4%	±0.83%	< 1.5%	> 270 lux

Product Availability

Sn10Pb90 solder spheres are sold in a minimum order quantity of 10,000 spheres, with volume supply to hundreds of millions of spheres. Stock diameters range from 0.002" to 0.035" (0.050 mm – 0.889 mm) with tight, industry-standard dimensional tolerances. Bulk jars and tape-and-reel formats are available.

Product Quality & Traceability

All EasySpheres product conforms to rigorous inspection requirements including sphere size and tolerance uniformity, sphericity, alloy purity (per IPC J-STD-006C), manufacturing date-to-shelf viability, and storage history. Full product-lot traceability is maintained for all products sold worldwide, and a Certificate of Conformance ships with every order. EasySpheres operates to an internal quality system and provides standard quality documentation upon request.

Regulatory Compliance

RoHS: This product contains lead above the 0.1% w/w limit of Directive 2011/65/EU and is not RoHS compliant as supplied. Certain applications may qualify for exemptions under Annex III of the Directive — including Exemption 7(a) for solders with high melting temperature containing 85% or more lead by weight, applicable to this alloy. Customers are responsible for confirming that a valid exemption covers their application. This product is supplied for exempted, non-EEE, and other non-RoHS applications.


REACH: This product contains lead (Pb), CAS No. 7439-92-1, above 0.1% w/w. Lead is listed on the ECHA Candidate List of Substances of Very High Concern; this information is communicated in accordance with REACH Article 33. Supply of these articles is not prohibited under REACH. Safe-handling information is provided in the SDS.

Conflict Minerals: Tin is sourced through smelters conformant with the Responsible Minerals Assurance Process (RMAP); CMRT available upon request.

Executed REACH, RoHS, and Conflict Minerals declarations (July 2026) are available at www.easyspheres.com.

Product Packaging

Spheres are stored and packaged in anti-static polypropylene jars with color-coded screw-top lids. Each jar contains a moisture-desiccant barrier to protect against relative-humidity fluctuation. Product labels include part number (SKU), quantity per jar, alloy, diameter in inches and millimeters, date of expiry, lot code number, and a scannable QR code.



Storage, Handling, and Shelf Life

Shelf life is 2 years from the sealed-jar born-on date when stored in original sealed packaging under appropriate conditions. Refrigeration is not recommended and does not extend shelf life. Containers should remain unopened and un-agitated during storage; normal room-temperature fluctuation does not affect shelf life. Avoid contaminating spheres through contact with foreign objects, fingers, or moisture.

Reflow Profile and Placement

Follow the reflow profile recommended by the flux or solder-paste manufacturer. This product is used in semiconductor packaging processes worldwide and is most commonly applied in automatic ball placement machines.

Health and Safety

This product may be hazardous to health or the environment during handling or use. Read the corresponding Safety Data Sheet, available at www.easyspheres.com, and adhere to all specified safety procedures before using this product.

Ordering

Sales and quotations: Online, sales@easyspheres.com • (858) 486-4068 • www.easyspheres.com